


**SIRIUS ENERGY STORAGE MODULE
TECHNICAL DATA SHEET**

Part Number: 3000-24-A-0.8C-TM-SD-A-X-X-CS | Version Date: July 2019



PERFORMANCE SPECIFICATIONS	Voltage (Nominal)	24 V _{dc}
	Maximum Charge Voltage	27 V _{dc}
	Discharge Cut-Off Voltage	22 V _{dc}
	Total Energy	3000 WH
	Maximum Charge Rate	100 A
	Maximum Discharge Rate	100 A
ENVIRONMENTAL SPECIFICATIONS	Cell Operating Temperature ¹	-30 °C to 80 °C
	Operating Humidity	Non-Condensing
MECHANICAL SPECIFICATIONS	Dimensions (w × d × h) mm	493 x 565 x 201
	Weight (Kg)	50
	Module Casing Material	Aluminum
	Terminal Type	Anderson Connector x1
SMART FEATURES	Monitoring Data	Total Cell Voltage, Current, Temperatures, SOC and Energy
	Remote Monitoring	Via Sirius View App
	Communication and Connectivity	USB Port/Ethernet
	Alarm	Audible alarm in the event of Over/under-Voltage, Over-Current, Over Temperature
SIRIUSVIEW SOFTWARE	Module Monitoring	Current, Voltage, Temperatures, Total Energy delivered, SOC, Graphs
	System Monitoring	Modules Monitoring (connected in parallel or series)

This technical data sheet may change without notice and at the sole discretion of Kilowatt Labs, Inc.

Solutions for: Microgrids | C&I and Residential Solar | Electric Vehicles | Utility Grade Storage

Kilowatt Labs, Inc. | www.kilowattlabs.com

**SIRIUS ENERGY STORAGE MODULE
TECHNICAL DATA SHEET**

Part Number: 3000-24-A-0.8C-TM-SD-A-X-X-CS | Version Date: July 2019

MODULE SERVICE LIFE	Projected Cycle Life ^{2,3}	1 million cycles
	Projected Calendar Life ^{3,4}	45 years
	Shelf Life ⁵	10 years
	Warehousing	Can be stored at any SOC without affecting cycle life
SAFETY PERFORMANCE	Over/under voltage	Hardware protection, Module shut down
	Over Current	Hardware protection, Module shut down
	Over temperature	Hardware protection, Module shut down
	Additional Safety	100A DC circuit breaker +10A bypass breaker + DC contactor protection
COMPLIANCE⁶ INFORMATION	EN55032:2015, EN55024:2010, EN61000-4-2:2009, EN61000 EN61000:2008+A2:2010	
PRECAUTIONS	Alarm	In case of alarm, immediately rectify/attend to the cause of the alarm.
	Physical Damage	In case the Module is physically damaged due to any event, do not install and energize the Module under any circumstances and contact your Reseller.
	Short Circuit	Ensure precautions to prevent short-circuit under all circumstances.
	Galvanic isolation	When connecting to external devices ensure that galvanic isolation does not exceed 1000V.
	Charge/Discharge Current	Under no circumstances must the charge/discharge current exceed 100A.
	Charging Voltage	Under no circumstances must the charging voltage exceed 27 V _{dc} for more than 60 seconds.
	Charge Cycle	During charge cycle ensure never to exceed constant voltage of 27 V _{dc} and constant current of 100A.
	Series Connection	<ul style="list-style-type: none"> • All Modules must be at 100% SOC before connecting in series. • A maximum of 16 Modules with Module Combiner can be connected in series. Please consult your Reseller when connecting the Modules in series.

**SIRIUS ENERGY STORAGE MODULE
TECHNICAL DATA SHEET**

Part Number: 3000-24-A-0.8C-TM-SD-A-X-X-CS | Version Date: July 2019

	Parallel Connection	There is no limit on the number of Modules that can be connected in parallel.
	Series-Parallel Connection	Modules cannot be connected in Series-Parallel combination under any circumstance.

¹The temperature range indicates the range in which the supercapacitor cells can operate. The performance of the cells may vary if they are continuously operated outside a temperature range of -10°C to 55°C, and/or at C-rates higher than the maximum charge/discharge rate specified in this spec sheet. The operating temperature range of the Module varies based on the application. If the Module is to be operated continuously outside a temperature range of -10°C to 55°C, and/or at C-rates higher than the maximum charge/discharge rate specified in the spec sheet, please consult Kilowatt Labs or its Reseller prior to deploying.

²Projected life of supercapacitor cells. Cycle life will vary if cycled more than 4 times a day.

³Additional terms and conditions, including a limited warranty, will apply at the time of purchase.

⁴Projected Calendar life of supercapacitor cells from the date of first operation.

⁵Shelf life is the life of the Module (in years) from the date it is manufactured to the time it is first operated.

⁶CE certification is completed for supercapacitor cells.

Product dimensions are for reference only unless otherwise identified and may change without notice.
For critical applications, please contact your Reseller.