

**SIRIUS ENERGY STORAGE MODULE  
TECHNICAL DATA SHEET**

Part Number: 7100-48-B-2C-M-SD-A-X-X-G | Version Date: April 2020



<b>PERFORMANCE SPECIFICATIONS</b>	Voltage (Nominal)	48 V <sub>dc</sub>
	Maximum Charge Voltage	54 V <sub>dc</sub>
	Discharge Cut-Off Voltage	44 V <sub>dc</sub>
	Total Energy	7100 WH
	*Maximum Charge Rate	296 A
	*Maximum Discharge Rate	296 A
<b>ENVIRONMENTAL SPECIFICATIONS</b>	Cell Operating Temperature <sup>1</sup>	-30 °C to 80 °C
	Operating Humidity	Non-Condensing
<b>MECHANICAL SPECIFICATIONS</b>	Dimensions (w × d × h) mm	608 x 530 x 345
	Weight (Kg)	125
	Module Casing Material	Aluminum
	Terminal Type	F08
<b>SMART FEATURES</b>	Monitoring Data	Total Cell Voltage, Individual Cell Voltages, Current, Temperatures, SOC and Energy
	Remote control (optional)	Via Sirius Remote Control
	Communication and Connectivity	USB Port
	Alarm	Audible alarm in the event of Over/under-Voltage, Over-Current, Over Temperature
	Dry Contacts × 4	DB9 port (Programmable <sup>7</sup> )

**SIRIUS ENERGY STORAGE MODULE  
TECHNICAL DATA SHEET**

Part Number: 7100-48-B-2C-M-SD-A-X-X-G | Version Date: April 2020

<b>SIRIUSVIEW SOFTWARE</b>	Module Monitoring	Current, Voltage, Individual Cell Voltage, Temperatures, Total Energy delivered, SOC, Graphs
	System Monitoring	Modules Monitoring (connected in parallel or series)
<b>MODULE SERVICE LIFE</b>	Projected Cycle Life <sup>2,3</sup>	1 million cycles
	Projected Calendar Life <sup>3,4</sup>	45 years
	Shelf Life <sup>5</sup>	10 years
	Warehousing	Can be stored at any SOC without affecting cycle life
<b>SAFETY PERFORMANCE</b>	Over/under voltage	Hardware protection, Module shut down
	Over Current	Hardware protection, Module shut down
	Over temperature	Hardware protection, Module shut down
	Additional Safety	125A 2P DC Circuit Breaker +10A bypass breaker + SSR Protection
<b>COMPLIANCE<sup>6</sup> INFORMATION</b>	EN55032:2015, EN55024:2010, EN61000-4-2:2009, EN61000 EN61000:2008+A2:2010	
<b>PRECAUTIONS</b>	Alarm	In case of alarm, immediately rectify/attend to the cause of the alarm.
	Physical Damage	In case the Module is physically damaged due to any event, do not install and energize the Module under any circumstances and contact your Reseller.
	Short Circuit	Ensure precautions to prevent short-circuit under all circumstances.
	Galvanic isolation	When connecting to external devices ensure that galvanic isolation does not exceed 1000V.
	Charge/Discharge Current	Under no circumstances must the charge/discharge current exceed 296 A.
	Charging Voltage	Under no circumstances must the charging voltage exceed 54 V <sub>dc</sub> for more than 60 seconds.
	Charge Cycle	During charge cycle ensure never to exceed constant voltage of 54 V <sub>dc</sub> and constant current of 296 A.
	Series Connection	<ul style="list-style-type: none"> <li>All Modules must be at 100% SOC before connecting in series.</li> <li>A maximum of 8 Modules with Module Combiner can be connected in series.</li> </ul>

This technical data sheet may change without notice and at the sole discretion of Kilowatt Labs, Inc.

Solutions for: Microgrids | C&I and Residential Solar | Electric Vehicles | Utility Grade Storage

Kilowatt Labs, Inc. | [www.kilowattlabs.com](http://www.kilowattlabs.com)

**SIRIUS ENERGY STORAGE MODULE  
TECHNICAL DATA SHEET**

Part Number: 7100-48-B-2C-M-SD-A-X-X-G | Version Date: April 2020

		Please consult your Reseller when connecting the Modules in series.
	Parallel Connection	There is no limit on the number of Modules that can be connected in parallel.
	Series-Parallel Connection	Modules cannot be connected in Series-Parallel combination under any circumstance.
<p><sup>1</sup>The temperature range indicates the range in which the supercapacitor cells can operate. The performance of the cells may vary if they are continuously operated outside a temperature range of -10°C to 55°C, and/or at C-rates higher than the maximum charge/discharge rate specified in this spec sheet. The operating temperature range of the module varies based on the application. If the module is to be operated continuously outside a temperature range of -10°C to 55°C, and/or at C-rates higher than the maximum charge/discharge rate specified in the spec sheet, please consult Kilowatt Labs or its Reseller prior to deploying.</p> <p><sup>2</sup>Projected life of supercapacitor cells. Cycle life will vary if cycled more than 4 times a day.</p> <p><sup>3</sup>Additional terms and conditions, including a limited warranty, will apply at the time of purchase.</p> <p><sup>4</sup>Projected Calendar life of supercapacitor cells from the date of first operation.</p> <p><sup>5</sup>Shelf life is the life of the module (in years) from the date it is manufactured to the time it is first operated</p> <p><sup>6</sup>CE certification is completed for supercapacitor cells.</p> <p><sup>7</sup>Programmable features can be activated to program for appropriate version of Sirius View software.</p> <p>Product dimensions are for reference only unless otherwise identified and may change without notice.</p> <p>For critical applications, please contact your Reseller.</p>		

\*Please note that the serial Numbers starting from KWL02048V0111190900238 to KWL02048V0111190900264 should not be charged and discharged above 250A.